

When Continuous hinge technology is not a requirement but safety is paramount the TS 50 Safeguard with 'anti finger trap' delivers all expectations with the advantage of economy when working with in tight budgets.

The TS 50 Safeguard is the fleet door option with safety in mind like other Whiting shutters from the tempsaver range the TS 50 Safeguard is proven as an infinitely robust shutter providing strength and reliability in the harshest of environments.



The fleet door option with safety in mind.



TS 50 Safeguard provides the fleet operator with one of the finest shutter doors for trucks and trailers carrying goods to ATP class 'C' specification.

- 50mm polyurethane (CFC) free foam insulation.
- All stainless Steel hardware and hinges.
- Long life sealed rollers with stainless steal shafts and noise reducing system.
- Aluminium 1.78mm ribbed extrusion inside and out to provide a tough long life.
- Polyester powder coating to any standard RAL colour (white RAL 9010 as standard inside and out.
- Incorporating "fingerguard" safety feature to prevent items
- being placed between the panels.
- Enclosed twin spring balancer for added reliability.
- Twin stainless steal cables.



Whiting Tempsaver 50safeguard






Dual durometer top seal for maximum thermal performance.



Enclosed spring balancer for added reliability and reduction of load contamination from rotating torsion springs.



Mounting angle & side seal. The side seals are effective throughout the full operating cycle.



Stainless steel end hinge and roller carrier. Removable cap allows roller change without removing hinge.



Large 50mm diameter steel roller for extra strength and long life.



Stainless steel top closure arm designed to eliminate the need for having two tracks to carry top section.



75.10 bzp



77 lock complete with keeper

Innovation on the Move