

Whiting provides the fleet operator with the finest doors available for trucks and trailers carrying goods which demand effective levels of temperature control.

The Whiting Tempsaver 50 is specifically designed for refrigerated transport. If you consider the huge investment represented in the cost of your vehicle and the value of your load, you owe it to your customers to specify an insulated shutter door of the highest pedigree – The Whiting Tempsaver 50, the door that combines the latest in design technology with precision engineering.

- Aluminium 1.78mm thick extrusions inside and out, reinforced at the hinge fastening points, provide an extremely tough and durable structure. Their design offers the added advantages of being able to accept straightforward application of paint and decals, whilst facilitating easy cleaning.
- No rivets on face of door to interfere with lettering or decals.
- 50mm foam-in-place urethane insulation.
- All panel joints are double sealed.
- Rigid bottom channel has thermal break across entire width of door.
- Twin spring balancer provide independent lifting capabilities for each individual cable.
- All rollers can be easily changed without removing hinges.
- Electro deposition ("E" coat) painting of door hardware gives the best available corrosion protection.




Whiting Tempsaver 50



Dual durometer top seal for maximum thermal performance.



Enclosed spring balancer for added reliability and reduction of load contamination from rotating torsion springs.



Mounting angle & side seal. The side seals are effective throughout the full operating cycle.



Nylon roller with bearings end hinge and roller carrier. Removable cap allows roller change without removing hinge.



Large 50mm diameter steel roller for extra strength and long life.

Stainless steel top closure arm designed to eliminate the need for having two tracks to carry top section.



75.10 bzp

Innovation on the Move

J R Industries Ltd

Caxton Place, Pentwyr Cardiff, CF23 8XN, United Kingdom. el: +44 (0) 29 2054 9966 ax: +44 (0) 29 2054 9046



All products produced by J R Industries carry ISO 9002 quality accreditation gained in December 1988.

www.jrindustries.co.uk