



**The Whiting Dry Freight** shutter is today's leader in its field with more sold world-wide than all other roll-up door sales put together.

The Whiting Dry Freight shutter is a robust and durable product with quality control in keeping with ISO 2002 being exercised throughout the manufacturing process.

The door slats are produced from the finest high quality WBP plywood. During the manufacturing process all slats are edge sealed to help prevent deterioration during service. Any core gaps on the edges of the slats are filled during manufacture and the external faces are provided with a high quality medium density overlay (MDO) for subsequent painting.

Whiting Dry Freight shutters are quick to fit and easy to maintain. They are the closure to specify when the requirement is for a robust hard wearing product that will work without trouble and the need for maintenance for a very long period.

Our cables are manufactured from high quality 49 strand (7x7) stainless steel wire. As part of our commitment to quality, cables are batch tested and certified to meet a breaking strain in excess of 500kg.

The Whiting Dry Freight shutter is available with different lock options, either the plant on type 77 lock or the spring assisted recessed type 70. The type 70 provides a greater degree of security for valuable loads and can be used in conjunction with Assa, Best or Yale type cylinder locks where required.

The Whiting Dry Freight shutter is produced in two different standard models for rear and side closures, namely:

- The 470 Normally incorporating four rows of hinges and a Whiting type 70 lock
- The 477 As the 470 but fitted with the type 77 in lieu of the type 70 lock

The Whiting Dry Freight shutter can be tailor made to your specific requirements.





Twin spring balancer

## Whiting Dry Freight 470



4 rows of hinges, 70 lock c/w Yale cylinder

## Whiting Dry Freight 477



4 rows of hinges, 77 lock



4 rows of blind fixing hinges for

smooth exterior, 70 lock c/w

Yale cylinder

4 rows of blind fixing hinges for smooth exterior, 77 lock

Split hinge





Silent running end hinge assy

adjuster







Caxton Place, Pentwyn, Cardiff, CF23 8XN, United Kingdom. Tel: +44 (0) 29 2054 9966 Fax: +44 (0) 29 2054 9046 e-mail: sales@jrindustries.co.uk or visit our website at www.jrindustries.co.uk



All products produced by JR Industries carry ISO 9002 quality accreditation gained in December 1988.

Centre hinge

